



- NOTES:
1. RECEIVER TUBE SHALL BE COVERED BY DUCT TAPE ON ALL SIDES.
  2. RECEIVER TUBE SHALL BE SET IN 22" OF CONCRETE UNLESS IN SIDEWALK.
  3. RECEIVER TUBES SET IN SIDEWALK SHALL HAVE 2 HOLES COMPLETELY ABOVE FINISHED SURFACE.
  4. IF RECEIVER TUBE IS SET IN SIDEWALK IT SHALL BE 2'-2" DEEP & BACKFILLED WITH COMPACTED FILL, THEN CONCRETE FROM BOTTOM TO TOP OF WALK.
  5. SIGN PLACEMENT IN SIDEWALK SHALL ALLOW FOR 5' CLEAR PASSAGE & EDGE OF SIGN SHALL BE 24" FROM FACE OF CURB.
  6. POST SHALL BE COATED WITH ANTI-SEIZE ON THE SECTION FITTED INSIDE THE RECEIVER TUBE.

RECEIVER TUBES			
POST SIZE	GAUGE	ANCHOR SIZE	CONCRETE SET DEPTH
≤10'	12 GA	2 1/4" X 24"	22"
12'	12 GA	2 1/4" X 30"	28"
14'	12 GA	2 1/2" X 36"	34"
16'-18'	7 GA	2 1/2" X 36"	34"

NTS

CITY OF SANDY

STANDARD SIGNPOST

PWS VERSION: JAN 2024

DRAWN	CM
REV. DATE	JAN 2019
APPR.	
DETAIL NO.	631